

DTCM230-150-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.076
Object Field of View (Φmm)	150
Working Distance (mm)	300±5
Max Sensor Size (Φmm)	11.4(2/3")
Best Aperture (F/#)	4.9
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>185
Depth of Field (mm)	±76.1@F11
Length of I/O (mm)	642±5

Field of View (mm × mm)	
8.47x7.1 with ICX625/655	111.5x93.4
Mechanical Specifications	
Mount	C
Length (mm)	324.0
Weight (kg)	5.7
Compatible Lighting	
Telecentric LED Lighting	DTCL-150-xW-y
	Beam Diameter 150mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

